

B	Tubing Connection Diameters (inches) [millimeters]								
	Model	Suction (Copper)	Liquid (Copper)	Condensat (Flexible PVC)					
	UNHA-09/12	1/2" [12.70]	1/4" [6.35]	1/2" i.d. [12.70]					
	UNHA-24	3/4" [19.05] *	3/8" [9.53]	1/2" i.d. [12.70]					
	LINIC Δ-36	3/4"	3/8"	1/2" i.d.					

7/8''

7/8''

→ 21/32" **→**

FROM SIDE OF CABINET * UNHA24 Suction connection size is 3/4" O.D. and must bush down to 5/8" at the UNHA indoor unit when matched with an 18,000 Btuh condenser or heat pump.

-7/8" x 7/8" CUTOUT LOCATED ON BOTTOM, RIGHT-FRONT CORNER OF CABINET

FOR CONDENSATE DRAIN TUBE ROUTING, WHEN UNIT IS IN CEILING MOUNTED

POSITION. (B)

DETAIL A

	Unit Weights								
Model	Unit (lbs.) [Kg]	Packaging (lbs.) [Kg]	Total Shipping Weight (lbs.) [Kg]						
UNHA-09	87	5	92						
	[39.46]	[2.27]	[41.73]						
UNHA-12	90	5	95						
	[40.82]	[2.27]	[43.09]						
UNHA-24	110	6	116						
	[49.89]	[2.72]	[52.61]						
UNCA-36	145	8	153						
	[65.77]	[3.63]	[69.40]						

		THIS DOCUMENT AND ITS CONTENTS CONSTITUTE PROPRIETARY TRADE SECRET. OF ECR INTERNATIONAL, INC. AND MAY NOT BE REPRODUCED, DISTRIBUTED OR USED IN ANY MANNER WITHOUT THE EXPRESS WRITTEN CONSENT OF AN AUTHORIZED REPRESENTATIVE OF ECR INTERNATIONAL, INC.					
			UNCA/UNHA CERTIFIED DRAWING (Engineering Specicifications)				
REVISIONS		SCALE		NONE	DATE 12 N	ЛAR. 07	
DATE	CN	DESCRIPTION	UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES	DRAWN BY	B.DOTE	CHECKED BY	J.HOYT
3/12/2007	070132	NEW RELEASE	TOLERANCES ARE: MAT'L N/A		N/A		
4/27/2007	070250	ADDED DETAIL-A, AND NOTATION ON LEADER FOR SAME. ADDED UNIT SIZES AND NOTE FOR BUSH DOWN TO TUBING CONNECTION DIAMETERS CHART	± 0.0156 ALL OTHER TOLERANCES ± 0.0313	DWG NO.	240006	707	REV B
	2		1				